

PRESSURE SWITCH EXPLOSION PROOF TYPE

PSA2000X

Explosion Proof Type
Protection: IP68
Proof Pressure to 3000psi
Adjustable Ranges: 10~1300psi
Temperature: -30 to 205°C
Dead Band: Adjustable

The New-Flow PSA2000X, an explosion proof pressure switch, is designed to be used in control systems. PSA2000X has high set point repeatability and adjustable dead band features. There are a variety of range selections available upon request. Easily adjusted to the set point, no special tools needed!

Technical Data

Switch Data: 20Amp @125, 250 or 480VAC; 5Amp, DC125V
Housing: die cast aluminum alloy with paint, and SS316 available
Conduit Connection: Female 3/4", 1/2" NPT, and M20 x P1.5 available
Pressure Element: welded type diaphragm
Process Material: wetted parts are all in SS316
Process Connection: Female 1/2" or 1/4" NPT, BSP, PT; and M20xP1.5 thread available

Range Selection Table

Code	Pressure Range	Adjustable Dead Band at "E" Position	Maximum Pressure Proof
10R	10~100 psi	10~25	3000 psi
20R	35~200 psi	12~30	3000 psi
30R	50~300 psi	28~50	3000 psi
60R	100~600 psi	28~60	3000 psi
130R	200~1300 psi	42~100	3000 psi

Ordering Information

PSA2000X	Code	Range				
		10R 10~100 psi	20R 35~200 psi	30R 50~300 psi	60R 100~600 psi	
		130R 200~1300 psi				
	Code	Wetted Parts Material				
	A	SS316				
	Code	Process Connection- Female				
		(1) 1/2" NPT (2) 1/4" NPT (3) 1/2" BSP (4) 1/4" BSP (5) 1/2" PT (6) 1/4" PT (7) M20 x P1.5				
	Code	Conduit Connection				
		(E) 3/4" NPT Female (F) 1/2" NPT Female, standard (G) M20 x P1.5 Female				
	Code	Switch Form				
	1	One SPDT				
	Code	Explosion Proof Type / Housing Material				
	A	<i>Certificate on Housing Only / Aluminum alloy:</i> Class I, Groups B, C & D; Class II, Groups E, F & G; NEMA 4, 7, 9				
	B / B1	<i>Taiwan Explosion Proof Certification / (B) Aluminum alloy (B1) SS316:</i> Ex d IIB + H2 T6 Gb				
	E	<i>International IECEx Certification / Aluminum alloy:</i> Ex db IIB + H2 T6 Gb; Ex tb IIIC T85°C Db				
	X	<i>Europe Union ATEX Certification / Aluminum alloy:</i> II 2 G D Ex db IIB + H2 T6 Gb; II 2 G D Ex tb IIIC T85°C Db				
	J	<i>Japan Explosion Proof Certification / Aluminum alloy:</i> Ex d IIB + H2 T6 Gb; Ex t IIIC T85°C Db				
	R	<i>Russia EACEx Certification / Aluminum alloy:</i> 1Ex d IIB + H2 T6 Gb X; Ex tb IIIC T85°C Db				

PSA2000X Complete Ordering Code



Approvals:

ABS
TYPE APPROVED PRODUCT

IEC **IECEx**

Ex **II2GD** **CE** 2503

TD0400TJ
工電(2012)第00320號
(ITRI)2017第07-00075號

JAPAN EX-Certificate
CML 17JPN1016X
CML 17JPN3024

Patent No.
M295332
M334932
China: 920135

Switches with
UL & CSA
Recognized
and File No.
E12252.

Dimensions

